Fred Kavli Theatre Technical Data



The Fred Kavli Theatre For The Performing Arts

Theatres Director:

Tel.

(805) 449-2767

E-Mail:

jserret@toaks.org

Technical Production Supervisor:Sean JonesTel:(805) 449-2739E-Mail:sjones@toaks.orgMailing Address:2100 Thousand Oaks Blvd.

Thousand Oaks, CA 91362

PARKING

Structure: Parking for - 723
Disabled - 24
Loading Dock: 24
Disabled - 1

AUDITORIUM SEATING

Maximum Capacity: 1800 Seats
Orchestra Pit Lift: 72 Seats/ 0 Wheelchairs
Orchestra Floor: 733 Seats/ 10 Wheelchairs
Founders Circle & Boxes: 191 Seats/ 4 Wheelchairs
Mezzanine & Boxes: 414 Seats/ 10 Wheelchairs
Balcony: 390 Seats/ 6 Wheelchairs
2 - Viewing Rooms; each: 9 Seats/ 1+ Wheelchairs

STAGE DIMENSIONS

Variable Proscenium Opening: 40' to 56' wide Proscenium Height: 35' Curtain Line to Upstage Wall (Stage Depth): 47' Curtain Line to Apron Edge: 10' Orchestra Lift Depth (On Centerline): 11'- 6" Stage Width: 118' Proscenium Arch to Stage Left Wall: 32' Proscenium Arch to Stage Right Wall: 30' 86'- 6" Grid Height: Scene Dock (Depth x Width): 26' x 60'

BACKSTAGE FACILITIES

Loading Dock Capacity: 3 Trailers/ Production Vans Loading Dock address: 225 S. Conejo School Road 91362 Green Room w/ kitchenette; Rehearsal/ Dance Warmup

STAGE DRAPERY	WIDTH	HEIGHT
House Curtain	73'	41'
Teaser	83'	20'
Border #1	83'	16'
Borders #2, 3, 4, 5, #6 - 60' x	10' 83'	10'
Legs (prs.) #1, 2, 3, 4, 5, 6	14'	32'
Midstage Traveler	68'	32'
Upstage Traveler	84'	32'
Scrim (Sharkstooth)	83'	31'
Sky Drop/ RP Screen	70'	36'
Tabs (2 Each)	33'	32'
Blackout Drops (2 Each)	44'	43'

RIGGING

- 1 Motorized Fire Curtain
- 2 Motorized Electric #1 & 2

Room (34' x 41') Including: mirrored wall, ballet bar, and sprung floor; Costume Maintenance Shop and Laundry Room; Road Manager's Office, Crew Office and Lounge.

DRESSING ROOMS

All dressing rooms have makeup mirrors, counters, wardrobe hanging racks, lockers, sink(s), toilet(s) and shower(s), and are served by elevator and staircases. Dressing rooms are ADA accessible, except as noted below.

Stage Right: Headliner Dressing Room (1 person)

Star Dressing Room #1 (2 person) Star Dressing Room #2 (3 person)

Quick Change Room (upstage right, 2 person)

Lower Level: 4 - Featured Player Dressing Rooms

(2 person, 2 are not ADA accessible)

1 - Small Chorus Dressing Room (17 person)1 - Large Chorus Dressing Room (33 person)

Makeup/Performer Stations: 64 total

ORCHESTRA PIT

80 Musician Capacity, in stepped pit. ADA Accessible.

ORCHESTRA PIT LIFT

Spiral Lift Type, with 50 lbs.sq.ft. live load lifting capacity at 8-10 feet per minute and 125 lbs.sq.ft. static carrying capacity. The Seating Wagon (Rows AA, BB & CC) is moved on air bearings.

ORCHESTRA SHELL

Encloses maximum 1550 square feet behind proscenium. Eleven floor-mounted, castered, nesting Side Towers store upstage in Scene Dock. Ceiling Panels and Clouds fly and store overhead.

HOUSE PIANOS

- 1 Steinway Model D 9' Concert Grand (A441)
- 1 Yamaha CFIII 9' Concert Grand/Midi Player (A440)
- 1 Yamaha CF-3 6'-1" Grand (In Founders Room)
- 1 Yamaha 48" Upright Rehearsal Piano
- 1 Kawai Upright Rehearsal Piano

FULLNESS	MAIERIAL	COLOR
75%	Velour	Red
Flat	Velour	Red
Flat	Velour	Black
Flat	Velour	Black
Flat	Velour	Black
50%	Velour	Black
50%	Velour	Black
Flat	Seamless	Black
Flat	Plastic	White
Flat	Velour	Black
Flat	Velour	Black

- 3 Motorized Shell Ceiling
- 3 Single Purchase Counterweight Shell Clouds
- 1 Single Purchase Cyc Electric

- 1 Double Purchase Sky Drop/ RP Screen
- 4 Double Purchase Counterweight Tab Battens
- 2 Single Purchase Counterweight Tab Battens
- 53 -Single Purchase Counterweight Linesets, including:
 - 1 House Curtain
 1 Projection Screen
 1 Midstage Traveler
 1 Upstage Traveler
 - 6 Borders 1 Scrim
 - 6 Legs (pairs) 33 General Purpose 1 - Concert Curtain 33 - 5/8" Spotting Blocks

ARBOR CAPACITIES

Tabs and Linesets:	1825#
Electrics:	2350#
Shell Clouds:	2350, 2405, 2870#
Counterweight Hoist:	1300#

Locking Rail and Loading Platform are Stage Right. Fly Floors are Stage Right and Left w/ Upstage Crossover.

LIGHTING THROW DISTANCES - To Curtain Line

Followspot Booth	120'
Mezzanine Control Room	106'
Balcony Front Rail	94'
Founders Circle/ Mezzanine Front Rail	64'
Lighting Catwalk #2	93'
Lighting Catwalk #1	75'
Side Slot #2	70' - 100'
Side Slot #1	30' - 70'

ROAD COMPANY & TELE-PRODUCTION ACCOMMODATIONS

- 1 Front-of-House Lighting Circuit Intercept Panel (Backstage Patch)
- 3 400 Amp Company Switches, 120/208VAC 3^e/4w bus connections and Posi-Lok Connections. D Stage L.
- 2 200 Amp Auxiliary Equipment Switches, 120/208VAC 3⁰/4w. with bus connections and Posi-Lok Receptacles. Upstage Left and Right.
- 1 200 Amp Road Sound Switch, with Power Sifter.
 Mid-Stage Left.
- 1 60 Amp Aux Switch, 120/208VAC 3^e/4w. with bus connections and Posi-Lok Receptacles. On Grid.
- 2 225 Amp Production Van Switches,120/208VAC
 3θ/4w. with bus connections, Posi-Lok Receptacles, & Power Sifter in the Loading Dock Vestibule.
- 1 Cable Trench from Loading Dock to Downstage Left.
- 1 Cable Tunnel from Downstage Left to Audio Mix Position at rear of Orchestra Floor. 150' run to FOH.

STAGE LIGHTING CONTROL SYSTEM

- 468 2.4KW Strand CD-80 Stage Dimmers
- 26 6.0KW Strand CD-80 Stage Dimmers
- 1 ETC ION 2000 Control Board w/ 2 x 20 fader wing.
- 1 ETC EOS Programming Wing
- ETCNomad Puck for remote monitoring at SR Stage Manager's Panel
- 2 Touch-screen monitors
- 1 Portable Lighting Designer's Remote Display
- 1 Wireless Focus Remote
- 3 DMX 512 Input: One at FOH in booth, one at S.M.P., one at A.S.M.P.

ONSTAGE FACILITIES

Compressed Air outlets in all four corners of stage. Service Sink - Upstage Left

30' x 50' area of stage floor is trappable to room below

LIGHTING INSTRUMENT INVENTORY

QT \ 2 2	'. - -	ITEM Follow Spotlights Follow Spotlights	LAMP HMI Xenon	WATTAGE 2.5KW 2.5KW	MAKE/ MODEL Lycian SuperStar 2.5 Model No. 1278 15 Strong Gladiator II
165 22 34 78 42 10 1 80 15	- - - - -	Source Four Bodies: Source Four 10° Lens tubes Source Four 19° Lens tubes Source Four 26° Lens tubes Source Four 36° Lens tubes Source Four 50° Lens tubes Source Four drop-in Iris Source 4 Pars- each with VNSP, N 6" Gel extenders	HPL SP, Med, & '	750 watt Wide lens	ETC
14 25	-	5° Colortran Ellipsoidal Spotlights 10° Strand Ellipsoidal Spotlights	FEL FEL	1k watt 1k watt	Colortran Model No. 650-082 Strand Model No. 2123
3	-	8" Fresnel Spotlights	BTN	1000 watt	Strand Model No. 3480
10	-	Cyc Floods, Iris 3, 3 circuit	FFT	1000 watt	Strand Model No. 5913 (12"x16" gel frame)

All units with color frame(s), safety cable(s), and 20amp Stage-Pin male theatrical connector(s). Pattern holders available for all types of fixture in varying numbers. A cable inventory is available for power and data purposes.

AUTOMATED LIGHTING - (Available at additional cost.)

10	High End Systems	SoloSpot 1000
10	High End Systems	SoloWash 37
1	Look Solutions	Unique 2.1 hazer
40'	Tomcat	Truss (black, 12"x18")
4	CM Lodestar	1 ton Chain Hoists

Motor cable and controller, data and power as required.

SOUND SYSTEM

MIXERS

1 – Digico SD8, digital mixing console w/built-in FX, comp, gate, EQ, 60 input capability.

1 - Mackie 16 Channel VLZ 1604 Mixer

FLOWN ARRAY

9 - L`Acoustics K2 Tri-amped, full range, per left and right array

12 - L'Acoustics KARA two-way center array

SUBS/INFILL (GROUND STACKS)

3 - L'Acoustic 2-way ARCHSWIDE per side

3 – L'Acoustics SB28 dual 18" sub per side

FRONT FILLS

6 - L'Acoustics 8XTi

AMPLIFIERS

11 – L'Acoustics LA8 1800 watt x 4 amplified controller. 1 – L'Acoustics LA4X 1000 watt x 4 channel amplified controller.

MONITOR

6 - JBL 805

2 - JBL 822

4 - JBL 826

4 - EAW JF100e

REPRODUCTION & PLAYBACK EQUIPMENT

- 1 Tascam CD-RW 402 Dual CD Player/Recorder
- 1 Tascam MD-350 Mini Disk Player/Recorder

MICROPHONES / DIRECT INPUT

2 - AKG 414

6 - Shure SM 81

5 - Crown PCC-160

9 - Shure 58 (Standard)

3 - Shure SM B58

2 - Shure Beta 57

6 - Shure Beta 57a

1 - Shure Beta 87a

1 - Shure 98

2 - Shure Beta 98

1 - Shure Beta 52

4 - Sennheiser 421

4 - Audio-Technica 853's

6 - Whirlwind passive Direct Input Boxes

INTERCOM SYSTEM

ClearCom - Backstage Program/ Page audio distribution. Two-channel common talk and signal light communication system. Each system with single and dual channel belt-pack stations, with headsets and extension cables; single and dual channel fixed stations.

PATCHING SYSTEMS

CCTV Video, Audio, and Effects Loudspeaker Patch

ACCESSORIES

Loudspeaker, Microphone, and Video Extension Cables Floor, Boom & Table Top Microphone Stands Storage Racks CDs

1 - Rapco 50' XLR, 12/8 snake

1 - Rapco 100' XLR, 12/8 snake

HEARING-IMPAIRED SYSTEM

'Listen' LT800 Transmitter 50- 'Listen' 72 MHZ Display Receivers

PROJECTION SCREENS

1 - 18'x24' front projection movie screen.

1 - 11'x14' front or rear projection Fast-Fold.

FRED KAVLI THEATRE

STAGE ELECTRICAL CIRCUIT SCHEDULE:

LOCATION FRONT-OF-HOUSE	2.4KW CIRCUITS	6.0KW CIRCUITS
Follow Spot Booth		469 - 470
Balcony Front	1 – 18	471 - 472
Loge/Mezzanine Front	19 - 36	473 - 474
Mezzanine Control Room		475 - 476
Main Floor Control Room	37 - 38	477 - 478
#2 Ceiling Catwalk	39 - 68	479 - 480
#1 Ceiling Catwalk	69 - 98	481 - 482
#1 Side Slot - House Right	99 - 106	
#2 Side Slot - House Right	107 - 114	
#1 Side Slot - House Left	115 - 122	
#2 Side Slot - House Left	123 - 130	
Orchestra Pit	131 - 142	
FRONT-OF-HOUSE		
INTERCEPT PANEL:	1 - 142	469 - 482
INTERCET TO ANY ELE	1 142	100 102
ON STAGE:		
Tormentor - Downstage Left	143 - 148	483 - 484
Floor Pockets - Stage Left 4@4	149 - 164	
PT Boxes - Stage Left 4@4	" "	
Tormentor - Downstage Right	165 - 170	485 - 486
Floor Pockets- Stage Right 4@4	171 - 186	
Up Stage Pigtail Boxes 4@4	187 - 202	
Fly Floor - Stage Left 2@6	203 - 214	
Tab Drop Boxes - S.L. 5@4	215 - 234	
Fly Floor - Stage Right 2@6	235 - 246	
Tab Drop Boxes - S.R. 5@4	247 - 266	
#1 Electric Pipe	267 - 302	487 - 488
#2 Electric Pipe	303 - 318	
S.L. Drop Boxes 9@6	319 - 372	
S.R. Drop Boxes 9@6	373 - 426	
#3 Electric Pipe - Sky Drops	427 - 456	
Upstage Scene Dock	457 - 464	489 - 492
Gridiron Pigtail Boxes	465 - 468	493 - 494

FRED KAVLI THEATRE

HOUSE RAIL SCHEDULE:

STAGE RAIL SCHEDULE:

#	FROM Plaster Line	PIPE NAME LENGTH (ext. =	accepts 3'-0" extension both ends.) (bri. ext. = accepts 3'-0" extension or 8'-0" bridled both ends.)		
1 4 5 6 7 8 9	1' - 0" 2' - 3" 3' - 3" 3' - 11" 4' - 7" 5' - 3" 6' - 0"	Red Valance House Curtain (May not be moved.) General Purpose (Border #1) General Purpose (Legs #1) General Purpose Electric #1 (Motorized Raceway) Shell Cloud #1 (Permanently installed) Shell Ceiling #1 (Permanently installed)	84' - 0" +ext. 84' - 0" +ext. 84' - 0" +ext. 68' - 0" Max. out trim: 43' 7" ed)		
11	6' - 11"	Electric #1a (Motorized Raceway)	68' - 0" Max. out trim: 43' 7"		
12	7' - 11"	General Purpose	68' - 0" +bri. ext.		
13	8' - 7"	General Purpose	68' - 0" +bri. ext.		
14	9' - 3"	General Purpose	68' - 0" +bri. ext.		
15	9' - 11"	General Purpose	68' - 0" +bri. ext.		
16	10' - 7"	General Purpose (Border #2)	68' - 0" +bri. ext.		
17	11' - 3"	General Purpose (Legs #2)	68' - 0" +bri. ext.		
18	11' - 11"	General Purpose	68' - 0" +bri. ext.		
19	12' - 7"	General Purpose	68' - 0" +bri. ext.		
20	13' - 3"	General Purpose (House Elect. #2)	68' - 0" +bri. ext.		
21	13' - 11" 14' - 7"	General Purpose	68' - 0" +bri. ext. 68' - 0" +bri. ext.		
22 23	14 - 7	General Purpose	33' - 8"		
24	 15' - 7"	Stage Left Tab Batten #1			
24A		Shell Ceiling #2 (Permanently install	Shell Cloud #2 (Permanently installed)		
25	16' - 7"	General Purpose	68' - 0" +bri. ext.		
26	17' - 3"	General Purpose	68' - 0" +bri. ext.		
27	17' - 11"	General Purpose	68' - 0" +bri. ext.		
28	18' - 7"	General Purpose (Border #3)	68' - 0" +bri. ext.		
29	19' - 3"	General Purpose (Legs #3)	68' - 0" +bri. ext.		
30	19' - 11"	General Purpose	68' - 0" +bri. ext.		
31	20' - 7"	General Purpose (House Elect. #3)	68' - 0" +bri. ext.		
32	21' - 3"	General Purpose	68' - 0" +bri. ext.		
33	21' - 11"	Mid-stage Traveler	68' - 0" +bri. ext.		
34	22' - 7"	General Purpose	68' - 0" +bri. ext.		
35	23' - 3"	General Purpose	68' - 0" +bri. ext.		
36	23' - 11"	General Purpose	68' - 0" +bri. ext.		
37		Stage Right Tab Batten #1 33' - 8"			
38	24' - 11"	Shell Cloud #3 (Permanently installed			
l 38A	25' - 4"	Shell Ceiling #3 (Permanently install	led)		

(RIGGING SCHEDULE CONTINUED)

```
25' - 11"
                      General Purpose (Border #4)
                                                             68' - 0" +bri. ext.
39
40
       26' - 7"
                      General Purpose (Legs #4)
                                                             68' - 0" +bri. ext.
41
       27' - 3"
                      General Purpose
                                                             68' - 0" +bri. ext.
42
       27' - 11"
                      General Purpose
                                                             68' - 0" +bri. ext.
43
       28' - 7"
                      General Purpose (House Elect. #4)
                                                             68' - 0" +bri. ext.
44
       29' - 3"
                      General Purpose
                                                             68' - 0" +bri. ext.
45
       29' - 11"
                      General Purpose
                                                             68' - 0" +bri. ext.
       30' - 7"
                      General Purpose
                                                             68' - 0" +bri. ext.
46
47
       31' - 3"
                      General Purpose
                                                             68' - 0" +bri. ext.
       31' -11"
                      General Purpose
48
                                                             68' - 0" +bri. ext.
49
       32' - 7"
                      General Purpose (Border #5)
                                                             68' - 0" +bri. ext.
       33' - 3"
50
                      General Purpose (Legs #5)
                                                             68' - 0" +bri. ext.
                                                             68' - 0" +bri. ext.
51
       33' - 11"
                      General Purpose (Black Scrim)
52
       34' - 7"
                      General Purpose
                                                             68' - 0" +bri. ext.
53
       35' - 3"
                      Cyclorama Electric (Raceway)
                                                             68' - 0"
                                                                          Max. out trim: 57'
54
       35' -11"
                      General Purpose
                                                             68' - 0" +bri. ext.
       36' - 7"
                                                             68' - 0" +bri. ext.
55
                      General Purpose
       37' - 3"
                      General Purpose
                                                             68' - 0" +bri. ext.
56
       37' - 11"
57
                      General Purpose (Border #6)
                                                             68' - 0" +bri. ext.
58
       38' - 7"
                      General Purpose (Legs #6)
                                                             68' - 0" +bri. ext.
       39' - 3"
59
                      General Purpose
                                                             68' - 0" +bri. ext.
       39' - 11"
                                                             68' - 0" +bri. ext.
60
                      General Purpose
       40' - 7"
                      General Purpose
                                                             84' - 0" +ext.
61
       41' - 3"
                      General Purpose
62
                                                             84' - 0" +ext.
63
       41' - 11"
                      General Purpose
                                                             84' - 0" +ext.
       42' - 7"
                      Upstage Traveler (May not be moved)84' - 0" +ext.
64
       43' - 3"
                                                             84' - 0" +ext.
65
                      Cvclorama
                                    (May not be moved.)
                      Stage Right Tab Batten #3
                                                             33' - 8" +ext.
67
            --
                                                             84' - 0" +ext.
68
                      Stage Right Tab Batten #2
69
                      Stage Left Tab Batten #2
                                                             84' - 0" +ext.
70
                      Stage Left Tab Batten #3
                                                             84' - 0" +ext.
71
                      (Located under upstage catwalk)
                                                             68' - 0" Manual Winch
                                                             54' - 0" Manual Winch
72
                      (Located over loading bay)
73
                      (Located over loading bay)
                                                             54' - 0" Manual Winch
```

Typical pipe is a 7-line set, lift lines 10' - 4" O.C.